P	Product No:		N18-1125-xCxx-x>	x,RevIR			model lis	sting			
		SPECIFICATIONS		PART#		Graduation	Dial Markings&	Sweep	Dial Te	xt	
		Fuel / Oil Quantity	N18 11	25 1C10 0	00	E, 1/4, 1/2, 3/4, F	B&W, 270°		Fuel (Qty	
		Type II (capacitive)									
built to meet or exceed AS 405B standards		N18 11	25 2C10 0	00	E, tick, 1/2, tick, F	B&W, 180°		Fuel (Qty		
Description:		Remote-indicating electronic quantity i	ndicator								
		w/ analog display									
Supply Voltage:		12 to 28 VDC (Nominal)									
		10 to 30 VDC (Max)									
Supply Current:		80-150 mA									
,											
Accuracy:		± 3% of full scale									
	,										
Sender input: capacitive probe (Voltage output) 0-5V,E-F		F-F									
•••••••			,								
DB-9 r	male Conne	ections									
1,2 Supply voltage (internally connected)											
	Regulated Voltage to Sender (+11V)										
	Not Used										
	Sender indicating signal										
6 Internal Lighting option											
	Internal Lighting option										
0,0											
		custom dial marking available									
Weigh	t:	4.0 oz									
						UMA Inc., Dayton VA 22821					
					Specification sheet Product # N18-1125-xCxx-xxx						
						-	Elec. Fuel Quant	Quantity, Capacitive Input			
REV	ECO	DESCRIPTION		DATE	DR	Drawn By: JM	Date: ######	Sheet	1 of 1	Rev.	IR